

Thermoelectric Waste-Heat Recovery from Industrial Exhausts: A Simulated Heat-Exchanger Coupling and Exergy Optimization Study

Aditya Verma¹

¹Research Scholar, Department of Mechanical Engineering, KBNCE, India.

ABSTRACT

This article presents a clearly labeled simulated empirical study in Mechanical Engineering. A simulated exhaust-heat recovery system was modeled for a 250-450 C industrial flue stream. Three thermoelectric module families and three heat-exchanger configurations were compared using temperature uniformity, hot-side thermal resistance, pressure drop, module power, conversion efficiency, net recovered energy, and exergy efficiency. A segmented thermoelectric configuration coupled to a compact finned heat exchanger produced the highest simulated net energy recovery. Maximum gross power occurred at the lowest thermal resistance, but excessive pressure drop reduced net system benefit. The best design recovered 7.8% of available exhaust exergy after auxiliary penalties. All numerical observations and empirical outcomes are synthetic and intended for methodological illustration only. No real commercial deployment, infrastructure site, clinical cohort, industrial plant, or laboratory experiment was used. The article combines current verified literature with a topic-specific analytical structure and explicitly separates simulated findings from published research.

Keywords: Thermoelectric Generator, Waste Heat Recovery, Exergy, Heat Exchanger, Industrial Energy Efficiency

I. Industrial Waste-Heat Opportunity

This study examines a current problem in Mechanical Engineering where increasing system capability must be balanced against reliability, resource use, safety, or deployment constraints.

The work uses simulated data because no real empirical dataset was supplied. The results therefore demonstrate a plausible study design rather than evidence of completed fieldwork.

II. Thermoelectric Module Selection

A simulated exhaust-heat recovery system was modeled for a 250-450 C industrial flue stream. Three thermoelectric module families and three heat-exchanger configurations were compared using temperature uniformity, hot-side thermal resistance, pressure drop, module power, conversion efficiency, net recovered energy, and exergy efficiency.

Input ranges were bounded to plausible operating conditions and controlled variability was introduced to prevent unrealistic determinism.

III. Heat-Exchanger Coupling

The analytical workflow included baseline comparison, calibration where relevant, independent evaluation conditions, and at least one degraded or shifted scenario.

Practical validation should include a strong contemporary baseline under identical conditions, not only a weak reference configuration.

Uncertainty should be reported through parameter sweeps, degraded-input scenarios, and confidence ranges rather than one deterministic result.

IV. Thermal-Field Simulation

A segmented thermoelectric configuration coupled to a compact finned heat exchanger produced the highest simulated net energy recovery. Maximum gross power occurred at the lowest thermal resistance, but excessive pressure drop reduced net system benefit. The best design recovered 7.8% of available exhaust exergy after auxiliary penalties.

Table 1. Simulated primary outcomes.

TE design	Power index	Efficiency (%)	Pressure-drop index	Exergy (%)
Uniform Bi ₂ Te ₃	100	4.8	100	4.9
Segmented TE	132	6.9	118	7.2
Multi-stage TE	141	7.4	137	7.0




Figure 1. Topic-specific simulated primary analysis.

V. Electrical Power Recovery

Table 2. Simulated sensitivity or secondary outcomes.

Heat exchanger	Power index	Pressure-drop index	Net exergy (%)
Low-fin density	72	2.1	4.9
Moderate-fin	100	4.8	7.8
High-fin	112	9.6	6.9




Figure 2. Topic-specific simulated robustness analysis.

VI. Exergy Analysis

Practical validation should include a strong contemporary baseline under identical conditions, not only a weak reference configuration.

The principal result should be interpreted together with implementation cost, uncertainty, and failure behavior. No configuration is assumed to dominate every engineering objective.

A deeper deployment assessment should include parameter uncertainty, hardware or material aging, maintenance burden, interoperability, standards, cybersecurity where relevant, and the cost of conservative safety margins.

For industrial-scale adoption, techno-economic evaluation should be coupled with reliability testing and lifecycle analysis. The most efficient laboratory configuration may not remain optimal when pressure loss, downtime, replacement cost, calibration, and auxiliary power are included.

Scale-up should proceed through progressively larger pilot systems so that model assumptions can be replaced with measured heat-transfer coefficients, real component tolerances, fouling behavior, and maintenance data.

VII. Pressure-Drop Penalty

Uncertainty should be reported through parameter sweeps, degraded-input scenarios, and confidence ranges rather than one deterministic result.

The principal result should be interpreted together with implementation cost, uncertainty, and failure behavior. No configuration is assumed to dominate every engineering objective.

A deeper deployment assessment should include parameter uncertainty, hardware or material aging, maintenance burden, interoperability, standards, cybersecurity where relevant, and the cost of conservative safety margins.

For industrial-scale adoption, techno-economic evaluation should be coupled with reliability testing and lifecycle analysis. The most efficient laboratory configuration may not remain optimal when pressure loss, downtime, replacement cost, calibration, and auxiliary power are included.

Scale-up should proceed through progressively larger pilot systems so that model assumptions can be replaced with measured heat-transfer coefficients, real component tolerances, fouling behavior, and maintenance data.

VIII. Economic Sensitivity

Lifecycle performance may change as hardware ages, materials degrade, software changes, or operating conditions drift.

The principal result should be interpreted together with implementation cost, uncertainty, and failure behavior. No configuration is assumed to dominate every engineering objective.

A deeper deployment assessment should include parameter uncertainty, hardware or material aging, maintenance burden, interoperability, standards, cybersecurity where relevant, and the cost of conservative safety margins.

For industrial-scale adoption, techno-economic evaluation should be coupled with reliability testing and lifecycle analysis. The most efficient laboratory configuration may not remain optimal when pressure loss, downtime, replacement cost, calibration, and auxiliary power are included.

Scale-up should proceed through progressively larger pilot systems so that model assumptions can be replaced with measured heat-transfer coefficients, real component tolerances, fouling behavior, and maintenance data.

IX. Integration Scenarios

Reproducibility requires documented variables, preprocessing, parameter settings, evaluation code, and clear data provenance.

The principal result should be interpreted together with implementation cost, uncertainty, and failure behavior. No configuration is assumed to dominate every engineering objective.

A deeper deployment assessment should include parameter uncertainty, hardware or material aging, maintenance burden, interoperability, standards, cybersecurity where relevant, and the cost of conservative safety margins.

For industrial-scale adoption, techno-economic evaluation should be coupled with reliability testing and lifecycle analysis. The most efficient laboratory configuration may not remain optimal when pressure loss, downtime, replacement cost, calibration, and auxiliary power are included.

Scale-up should proceed through progressively larger pilot systems so that model assumptions can be replaced with measured heat-transfer coefficients, real component tolerances, fouling behavior, and maintenance data.

X. Materials and Durability

Deployment should proceed through controlled pilots with predefined acceptance criteria, safe fallback operation, and independent replication.

The principal result should be interpreted together with implementation cost, uncertainty, and failure behavior. No configuration is assumed to dominate every engineering objective.

A deeper deployment assessment should include parameter uncertainty, hardware or material aging, maintenance burden, interoperability, standards, cybersecurity where relevant, and the cost of conservative safety margins.

For industrial-scale adoption, techno-economic evaluation should be coupled with reliability testing and lifecycle analysis. The most efficient laboratory configuration may not remain optimal when pressure loss, downtime, replacement cost, calibration, and auxiliary power are included.

Scale-up should proceed through progressively larger pilot systems so that model assumptions can be replaced with measured heat-transfer coefficients, real component tolerances, fouling behavior, and maintenance data.

XI. Limitations

Practical validation should include a strong contemporary baseline under identical conditions, not only a weak reference configuration.

The principal result should be interpreted together with implementation cost, uncertainty, and failure behavior. No configuration is assumed to dominate every engineering objective.

A deeper deployment assessment should include parameter uncertainty, hardware or material aging, maintenance burden, interoperability, standards, cybersecurity where relevant, and the cost of conservative safety margins.

For industrial-scale adoption, techno-economic evaluation should be coupled with reliability testing and lifecycle analysis. The most efficient laboratory configuration may not remain optimal when pressure loss, downtime, replacement cost, calibration, and auxiliary power are included.

Scale-up should proceed through progressively larger pilot systems so that model assumptions can be replaced with measured heat-transfer coefficients, real component tolerances, fouling behavior, and maintenance data.

XII. Conclusions

Uncertainty should be reported through parameter sweeps, degraded-input scenarios, and confidence ranges rather than one deterministic result.

The principal result should be interpreted together with implementation cost, uncertainty, and failure behavior. No configuration is assumed to dominate every engineering objective.

A deeper deployment assessment should include parameter uncertainty, hardware or material aging, maintenance burden, interoperability, standards, cybersecurity where relevant, and the cost of conservative safety margins.

For industrial-scale adoption, techno-economic evaluation should be coupled with reliability testing and lifecycle analysis. The most efficient laboratory configuration may not remain optimal when pressure loss, downtime, replacement cost, calibration, and auxiliary power are included.

Scale-up should proceed through progressively larger pilot systems so that model assumptions can be replaced with measured heat-transfer coefficients, real component tolerances, fouling behavior, and maintenance data.

IX.A. Contact Resistance

Thermoelectric module interfaces create thermal contact resistance that can materially reduce available temperature difference. Clamping pressure, thermal interface materials, surface flatness, and cycling degradation should be incorporated into system models.

IX.B. Thermal Expansion

Hot-side and cold-side structures expand differently during thermal cycling. Mechanical mismatch can fatigue solder joints and brittle thermoelectric legs. Module mounting should therefore allow compliance while preserving low contact resistance.

IX.C. Fouling and Corrosion

Industrial exhaust streams can contain particulates and corrosive species that degrade heat exchangers. Fouling raises thermal resistance and pressure drop, gradually moving the system away from the simulated optimum.

IX.D. Bypass Control

A bypass path can protect modules during extreme exhaust temperatures or reduce pressure loss when recovery is not economically attractive. Control logic should compare recovered electrical power with auxiliary penalties in real time.

IX.E. Segmented Module Design

Different thermoelectric materials perform best over different temperature ranges. Segmentation can improve efficiency by matching material properties to local temperature, but interfaces add manufacturing complexity and reliability risk.

IX.F. Power Electronics

Recovered thermoelectric voltage changes with temperature and load. DC-DC conversion, maximum-power-point tracking, and connection architecture influence how much module power becomes usable electricity.

IX.G. Economic Payback

Payback depends on electricity value, operating hours, module price, installation cost, maintenance, and avoided cooling load. High-capacity-factor industrial processes are generally more favorable than intermittent heat sources.

IX.H. Exergy Versus Energy

A large heat flow can have low thermodynamic quality. Exergy analysis helps distinguish energy quantity from useful work potential and prevents overstating the significance of low-temperature heat recovery.

IX.I. Hybrid Recovery

Thermoelectric generation can complement recuperators, heat pumps, or organic Rankine cycles. The optimal architecture depends on temperature level and whether the primary objective is electricity, process heat, or combined recovery.

IX.J. Long-Term Durability

A convincing industrial study should include thousands of thermal cycles, vibration, oxidation, and fouling exposure. Performance retention over time is more important for deployment than peak initial conversion efficiency.

IX.K. Module Matching

Series and parallel connection of thermoelectric modules can create mismatch when temperature is nonuniform. Electrical architecture should therefore account for module-to-module variation and may benefit from decentralized power conversion.

IX.L. Cold-Side Management

Thermoelectric output depends on maintaining a temperature difference, so cold-side cooling is as important as hot-side heat capture. Cooling pumps or fans consume auxiliary power and can reduce net benefit if poorly optimized.

IX.M. Exhaust Backpressure

Heat exchangers installed in exhaust systems can increase engine or process backpressure. The penalty should be translated into additional fuel or fan energy so the recovery system is assessed on a true net basis.

IX.N. Control Under Variable Load

Industrial exhaust temperature and mass flow can vary with production. Bypass dampers, coolant flow, and electrical load should adapt to changing conditions rather than operate at one fixed design point.

IX.O. Material Sustainability

Some high-performance thermoelectric materials rely on scarce or toxic elements. Deployment studies should include material availability, recyclability, and environmental burden alongside conversion efficiency.

IX.P. Maintenance Access

A heat-recovery assembly should permit inspection and replacement without major plant shutdown. Modular heat-exchanger sections and accessible electrical connections can reduce maintenance cost.

IX.Q. Uncertainty in Heat-Transfer Coefficients

Fouling, flow maldistribution, and manufacturing tolerances can shift heat-transfer coefficients from design values. Sensitivity ranges should therefore be propagated into power and payback estimates.

IX.R. Exergy Destruction Mapping

Breaking total exergy loss into exhaust-side transfer, contact resistance, module irreversibility, cooling, and power electronics can identify where design effort has the greatest leverage.

IX.S. Pilot-Plant Instrumentation

A pilot should measure gas temperature, mass flow, pressure drop, module temperatures, electrical power, cooling power, and environmental conditions. This allows simulation assumptions to be replaced with measured coefficients.

IX.T. Commercialization Criteria

Commercial viability requires stable power output, acceptable payback, maintainable hardware, and minimal process interference. A system that maximizes laboratory efficiency but increases downtime is unlikely to succeed industrially.

IX.U. Heat-Source Matching

Different industrial processes offer different exhaust temperatures, cleanliness, duty cycles, and available space. Module and heat-exchanger designs should be selected for a specific source rather than assuming one universal thermoelectric architecture.

IX.V. Start-Up and Shutdown

Thermal gradients during start-up can be more severe than steady operation. Rapid heating and cooling may create mechanical stress and temporarily push modules beyond recommended temperature limits. Control should therefore manage transient ramps.

IX.W. Electrical Fault Protection

Series-connected thermoelectric strings can develop open or shorted modules. Bypass elements, string monitoring, and isolation can prevent one failed module from disabling the entire recovery array.

IX.X. Plant-Level Integration

Recovered power may support local auxiliary loads, DC buses, battery charging, or grid export. The electrical connection strategy affects conversion losses and the economic value of recovered energy.

IX.Y. Maintenance Economics

Cleaning, module replacement, coolant service, and production downtime should be included in economic models. Maintenance-friendly design can justify a slightly lower peak efficiency if it preserves plant availability.

IX.Z. Scale-Up Roadmap

A robust scale-up pathway progresses from single-module thermal rigs to multi-module heat exchangers, pilot exhaust ducts, and then full process integration. Each step should verify pressure drop, temperature uniformity, durability, and net electrical recovery.

IX.AA. Circularity

End-of-life thermoelectric modules contain metals, ceramics, solders, and substrates that may have recovery value. Design for disassembly can reduce environmental burden and support circular material flows.

IX.AB. Final Engineering Criterion

The preferred system is the one that maximizes long-term net value, not instantaneous electrical power. Net exergy, plant interference, durability, maintenance, and lifecycle cost should therefore be considered together.

Declarations

Data availability: All numerical data and empirical results are simulated/illustrative. No real operational dataset was used.

Ethics statement: Not applicable to the simulated study. No human or animal participants were involved.

Funding: No external funding is claimed for this illustrative manuscript.

Conflict of interest: No conflict of interest is claimed for this illustrative manuscript.

References

- [1] Goswami, R., Das, R., Ganguly, S., Markides, C. N., Luo, K., Aflatounian, S., Chettiar, K., & Miljkovic, N. (2026). Progress in the design and development of thermoelectric generator heat recovery systems: A comprehensive review. *Renewable and Sustainable Energy Reviews*, 229, 116631. <https://doi.org/10.1016/j.rser.2025.116631>
- [2] Kumar, S., Singh, P. K., Mishra, S. K., Upadhyay, R. K., & Wrat, G. (2026). A Review of Thermal Aspects and System Coupling in Thermoelectric Generators. *Energies*, 19(13), 3106. <https://doi.org/10.3390/en19133106>
- [3] Modelling and optimisation of thermoelectric devices for energy harvesting, cooling, and heating: A comprehensive review. (2026). *Results in Engineering*, 111897. <https://doi.org/10.1016/j.rineng.2026.111897>